




State of the Art, Inc.

Thin Film Chip Resistor

M55342/04 RM1505







PERFORMANCE

Resistance Range **100Ω - 1MΩ**
 Tolerances **0.1%, 1%, 2%, 5%**
 Maximum Power **150 mW**
 Maximum Voltage **125 Volts**

TESTS	CHARACTERISTICS*	
	E	H
TCR (-55 to +125 °C) in ppm/°C	±25	±50
Thermal Shock	±0.1%	±0.25%
Low Temperature Operation	±0.1%	±0.25%
Short-time Overload	±0.1%	±0.1%
Resistance to Soldering Heat	±0.2%	±0.25%
Moisture Resistance	±0.2%	±0.4%
Life, 2,000 Hours	±0.5%	±0.5%
High Temperature Exposure	±0.1%	±0.2%

*Maximum allowable change per MIL-PRF-55342, typical change is 10% of these values.



PART NUMBERING

M55342 H 04 B 100D R - TR

PACKAGING CODE: TR = Tape & Reel W= Waffle Pack

PRODUCT LEVEL DESIGNATOR: M: 1% per 1000 hrs. R: 0.01% P: 0.1% T: Space Level C: Non - ER

RESISTANCE AND TOLERANCE CODE:

Three significant digits, with a letter indicating the decimal location, the tolerance, and the value range.

A: 0.1% Ω D: 1% Ω G: 2% Ω J: 5% Ω
 B: 0.1% KΩ E: 1% KΩ H: 2% KΩ K: 5% KΩ
 C: 0.1% MΩ F: 1% MΩ T: 2% MΩ L: 5% MΩ

TERMINATION MATERIALS: B: Solderable wraparound W: Gold wire bondable

SIZE CODE: /04 = RM1505


TEMPERATURE CHARACTERISTIC: E: ± 25ppm H: ± 50ppm

PERFORMANCE SPECIFICATION MIL-PRF-55342

MECHANICAL

	INCHES	MILLIMETERS
Length	.150 (.148 - .162)	3.81 (3.76 - 4.11)
Width	.048 (.045 - .055)	1.22 (1.14 - 1.40)
Thickness	.023 (.015 - .033)	0.58 (0.38 - 0.84)
Top Term	.015 (.010 - .020)	0.38 (0.25 - 0.51)
Bottom Term	.014 (.010 - .020)	0.36 (0.25 - 0.51)
Gap	.122 (.118 - .126)	3.10 (3.00 - 3.20)
Approx. Weight	.0097 grams	

MINIMUM RECOMMENDED MOUNTING PADS (INCHES)



State of the Art, Inc. 2470 Fox Hill Road, State College, PA 16803-1797
 Phone (814) 355-8004 Fax (814) 355-2714 Toll Free 1-800-458-3401

04/09/08

Specifications subject to change without notice.

www.resistor.com