5°

State of the Art, Inc. 0502 Thick Film Chip Resistor

Standard Grade, Wraparound



PERFORMANCE CHARACTERISTICS

Resistance Range Tolerances (1) TCR Thermal Resistance Maximum Power Maximum Voltage 1Ω-40MΩ 1%, 2%, 5%, 10% ±100, ±200, ±300 ppm 85.3°C/W 60 mW 40 Volts

ENVIRONMENTAL PERFORMANCE (1)

Thermal Shock	±0.03%
Low Temperature Operation	±0.03%
Short-time Overload	±0.03%
Resistance to Bonding Exposure	±0.03%
Moisture Resistance	±0.05%
High Temperature Exposure	±0.05%
Life Test	See Chart

(1)Typical resistance change, test methods and criteria







POWER DERATING

LIFE TEST



PART NUMBERING

per MIL-PRF-55342.

S 0502 C P X 150 J 20 - TR

			PACKAGING CODE: - TR = Tape/Reel - W = Waffle Carrier (Default packaging is Bulk)					
		TEMPERATURE CHARACTERISTIC: 10: ±100 ppm 20: ±200 ppm 30: ±300 ppm						
			TOLERANCE: F: 1% G: 2% J: 5% K: 10% M: 20%					
			RESISTANCE VALUE: Four digits are used for tolerances of 1% or lower, three digits are used above 1%. Leading digits are significant while the last digit specifies the number of zeros to add. The letter "R" is used to represent the decimal for fractional ohmic values. Example: 5R6 is 5.6 ohms.					
		-	TERMINATION FINISH: X: Sn60 over Nickel (Solderable) C: Silver bearing (Epoxy bondable-RoHS) G: Gold (Epoxy bondable-RoHS) Y: Silver over Nickel (Solderable -RoHS) Z: Gold over Nickel (Solderable-RoHS)					
		PRODUCT DESIGNATION: P: Thick film on alumina U: Untrimmed alumina (10% & 20% tolerance only)						
	TERMINATION TYPE: C: Wraparound termination							
SIZE CODE								
GRAD	GRADE: S: Standard Production H: High Reliability (For Screening options, contact the factory)							

MECHANICAL

	INCHES MILLIN	METERS	.082 ———			
Length Width Thickness Top Term Bottom Term Gap Approx. Weight	.052 (.050060) 1.32 (1.2 .025 (.023027) 0.64 (0.5 .018 (.013023) 0.46 (0.3 .009 (.005015) 0.23 (0.1 .014 (.010020) 0.36 (0.2 .024 (.020028) 0.61 (0.5 .00155 grams	27 - 1.52) MINIMUM 58 - 0.69) RECOMMENDED 33 - 0.58) MOUNTING 13 - 0.38) PADS 25 - 0.51) (INCHES) 51 - 0.71)				
"Specifications subject to change without notice."						

STATE OF THE ART, INC. 2470 Fox Hill Road, State College, PA 16803-1797 Phone (814) 355-8004 Fax (814) 355-2714 Toll Free 1-800-458-3401 www.resistor.com

02/08/08