
State of the Art, Inc.

Zero Ohm Chip Resistor





Performance

100 mW Power Rating -65 to 150°C Operating Range **Product Levels** M & T

С **Termination Material** G U **Current Rating** 2.2 A 1.8 A 1.0 A Maximum Resistance 0.020Ω 0.030Ω 0.100Ω

MIL-PRF-32159 provides zero ohm chip resistors (jumpers) at two product levels: miltary M and space level T. Both levels are subject to Group A, B, and C lot acceptance testing. While Group C does include a 2000 hour life test, it does not accumulate enough unit hours to provide an established reliability failure rate level.

Military level M is subject to Group A on a production lot basis while Groups B and C are performed on an inspection lot basis.

Space level T is subject to Groups A and B on a production lot basis while Group C is performed on an inspection lot basis. Group A includes 100% power conditioning to screen infant mortality.

Lot Acceptance Testing


Group A Precap Visual Thermal Shock **Power Conditioning** (space level only) DC Resistance Visual Inspection


Group C Life (2000 hours) Thermal Shock Solderability Low Temperature Operation Resistance to Solvents Resistance to Mounting Moisture Resistance High Temperature Exposure

Group B

Short Time Overload

Mounting Integrity





Part Number

M32159C02M -TR

Packaging: -TR: Tape & Reel -W: Waffle Tray

Product Level: M: Military T: Space

Size: 02: RCZ0505

Termination Material: C: Epoxy Bondable Silver U: Epoxy Bondable Platinum Gold G: Epoxy Bondable Gold

Performance Specification MIL-PRF-32159

Mechanical

.082 Millimeters Inches Length (a) .052(.049 - .061) 1.32(1.24 - 1.55) Width (b) .048(.045 - .055) 1.22(1.14 - 1.40)Recommended Thickness (c) .018(.012 - .033) 0.46(0.30 - 0.84)Minimum 054 Top Termination (d) .009(.005 - .015) 0.23(0.13 - 0.38)**Bond Pads** .014(.010 - .020) Bottom Termination (e) 0.36(0.25 - 0.51)(inches) Approximate Weight 0.00315 g **⊢** .031 **+ ⊢** .020 **− ·**

State of the Art, Inc. 2470 Fox Hill Road, State College, PA, USA 16803-1797 www.resistor.com Telephone: 814-355-8004 Toll Free: 800-458-3401 Fax: 814-355-2714