
State of the Art, Inc. Zero Ohm Chip Resistor

MIL-PRF-32159/06 Epoxy Bondable RCZ0705



Performance

Power Rating 150 mW
Operating Range -65 to 150°C
Product Levels M & T

Termination Material G C U Current Rating 2.7 A 2.2 A 1.2 A Maximum Resistance 0.020Ω 0.030Ω 0.100Ω

MIL-PRF-32159 provides zero ohm chip resistors (jumpers) at two product levels: miltary M and space level T. Both levels are subject to Group A, B, and C lot acceptance testing. While Group C does include a 2000 hour life test, it does not accumulate enough unit hours to provide an established reliability failure rate level.

Military level M is subject to Group A on a production lot basis while Groups B and C are performed on an inspection lot basis.


Space level T is subject to Groups A and B on a production lot basis while Group C is performed on an inspection lot basis. Group A includes 100% power conditioning to screen infant mortality.


Lot Acceptance Testing

Group A
Precap Visual
Thermal Shock
Power Conditioning
(space level only)
DC Resistance
Visual Inspection
Solderability
Resistance to Solvents

Group B Short Time Overload Mounting Integrity

Group C
Life (2000 hours)
Thermal Shock
Low Temperature Operation
Resistance to Mounting
Moisture Resistance
High Temperature Exposure





Part Number

M32159C06M -TR

Packaging: -TR: Tape & Reel -W: Waffle Tray

Product Level: M: Military T: Space

Size: 06: RCZ0705

Termination Material: C: Epoxy Bondable Silver U: Epoxy Bondable Platinum Gold G: Epoxy Bondable Gold

Performance Specification MIL-PRF-32159

Mechanical

.105 Millimeters Inches Length (a) .075(.074 - .086) 1.91(1.88 - 2.18) Width (b) .048(.045 - .055) 1.22(1.14 - 1.40) Recommended Thickness (c) .018(.015 - .033) 0.46(0.38 - 0.84)Minimum 054 Top Termination (d) .012(.008 - .024) 0.30(0.20 - 0.61)**Bond Pads** .014(.010 - .020) 0.36(0.25 - 0.51) Bottom Termination (e) (inches) Approximate Weight 0.00405 g ⊢ .031 + .043 -

State of the Art, Inc. 2470 Fox Hill Road, State College, PA, USA 16803-1797 www.resistor.com Telephone: 814-355-8004 Toll Free: 800-458-3401 Fax: 814-355-2714