


State of the Art, Inc.

Zero Ohm Chip Resistor





Performance

Power Rating 150 mW Operating Range -65 to 150 °C Product Levels M & T Current Rating 2.1 A Maximum Resistance 0.035 Ω

MIL-PRF-32159 provides zero ohm chip resistors (jumpers) at two product levels: miltary M and space level T. Both levels are subject to Group A, B, and C lot acceptance testing. While Group C does include a 2000 hour life test, it does not accumulate enough unit hours to provide an established reliability failure rate level.

Military level M is subject to Group A on a production lot basis while Groups B and C are performed on an inspection lot basis.


Space level T is subject to Groups A and B on a production lot basis while Group C is performed on an inspection lot basis. Group A includes 100% power conditioning to screen infant mortality.


Lot Acceptance Testing

Group A
Precap Visual
Thermal Shock
Power Conditioning
(space level only)
DC Resistance
Visual Inspection
Solderability
Resistance to Solvents

Group B Short Time Overload Mounting Integrity

Group C
Life (2000 hours)
Thermal Shock
Low Temperature Operation
Resistance to Mounting
Moisture Resistance
High Temperature Exposure





Part Number

M32159B04M -TR

Packaging: -TR: Tape & Reel -W: Waffle Tray

Product Level: M: Military T: Space

Size: 04: RCZ1505

Termination Material: B: Solderable (SnPb solder over nickel)

Performance Specification MIL-PRF-32159

Mechanical

.190 Inches Millimeters Length (a) .150(.148 - .162) 3.81(3.76 - 4.11) Width (b) .048(.045 - .055) 1.22(1.14 - 1.40)Recommended Thickness (c) .023(.015 - .033) 0.58(0.38 - 0.84)Minimum 054 Top Termination (d) .015(.010 - .020) 0.38(0.25 - 0.51)**Bond Pads** .014(.010 - .020) 0.36(0.25 - 0.51) Bottom Termination (e) (inches) Approximate Weight 0.00970 g <u>⊢ .037</u> **+** .116 **—** .

State of the Art, Inc. 2470 Fox Hill Road, State College, PA, USA 16803-1797 www.resistor.com Telephone: 814-355-8004 Toll Free: 800-458-3401 Fax: 814-355-2714