




State of the Art, Inc.

Semi-Precision Thick Film Chip Resistor



MIL-PRF-55342/11 Epoxy Bondable RM0402



Performance



Resistance Range*	1Ω to 22 MΩ
Tolerances (± %)*	1, 2, 5, 10
TCR (± ppm/°C)*	100, 200, 300
Power Rating	50 mW
Voltage Rating	30 V
Operating Range	-65 to 150°C
Product Levels	M, P, R, S, U, V, T

*see QPL55342 for part number availability



Maximum Allowable Drift

Temperature Characteristic	K	L	M
TCR (ppm/°C)	±100	±200	±300
Thermal Shock	±0.5%	±0.5%	±0.5%
Power Conditioning	±0.5%	±0.5%	±0.5%
Low Temperature Operation	±0.25%	±0.25%	±0.5%
Short Time Overload	±0.25%	±0.25%	±0.5%
High Temperature Exposure	±0.5%	±0.5%	±1.0%
Moisture Resistance	±0.5%	±0.5%	±0.5%
Life (Qualification)	±0.5%	±0.5%	±2.0%
Life (FR Level)	±2.0%	±2.0%	±2.0%
Resistance to Soldering Heat	±0.25%	±0.25%	±0.25%
Resistance to Bonding Exposure	±0.25%	±0.25%	±0.25%



Part Number

M55342K11B100DS -W

Packaging: -TR: Tape & Reel -W: Waffle Tray

Product Level (/1000 hrs.): M: 1% P: 0.1% R & U: 0.01% S & V: 0.001% T: Space 0.001%

Resistance Value and Tolerance: Ω: D: 1% G: 2% J: 5% M: 10%
 Three numerals and a letter indicating decimal, value range, and tolerance kΩ: E: 1% H: 2% K: 5% N: 10%
 MΩ: F: 1% T: 2% L: 5% P: 10%

Termination Material: C: Epoxy Bondable Silver U: Epoxy Bondable Platinum Gold G: Epoxy Bondable Gold

Size: 11: RM0402

Temperature Characteristic (ppm/°C): K: ±100 L: ±200 M: ±300


Performance Specification MIL-PRF-55342

Mechanical

	Inches	Millimeters
Length (a)	.042(.034 - .050)	1.07(0.86 - 1.27)
Width (b)	.022(.017 - .027)	0.56(0.43 - 0.69)
Thickness (c)	.018(.010 - .033)	0.46(0.25 - 0.84)
Top Termination (d)	.007(.005 - .015)	0.17(0.13 - 0.38)
Bottom Termination (e)	.008(.005 - .015)	0.20(0.13 - 0.38)

Approximate Weight 0.00108 g

Recommended Minimum Bond Pads (inches)



State of the Art, Inc. 2470 Fox Hill Road, State College, PA, USA 16803-1797
 www.resistor.com Telephone: 814-355-8004 Toll Free: 800-458-3401 Fax: 814-355-2714

Specifications Subject to Change Without Notice All Products Made in the USA Copyright 2015 by State of the Art, Inc.